






SCHEDA TECNICA TESSUTO (FABRIC SPECIFICATIONS)

NOME (NAME)	OUTDOOR
-------------	---------

	METODO (METHOD)	VALORI (VALUE)
COMPOSIZIONE (COMPOSITION)		89%PVC 4%CO 7%PE
ALTEZZA (WIDTH)	UNI EN 1773:1998	140 cm
PESO (WEIGHT)	UNI 5114:1982	830 g/m ²
MARTINDALE	UNI EN ISO 12947-2:2000	40.000 giri (turns)
PILLING TEST	UNI EN ISO 12945-2:2002 5000 CYCLES	--
SOLIDITA' ALLA LUCE (COLOURFASTNESS TO LIGHT)	UNI EN ISO 105-B02:2001	• 6
SOLIDITA' ALLO SFREGAMENTO (COLOURFASTNESS TO CROCKING) – SECCO (DRY)	UNI EN ISO 105-X12:2003	--
SOLIDITA' ALLO SFREGAMENTO (COLOURFASTNESS TO CROCKING) – UMIDO (WET)	UNI EN ISO 105-X12:2003	--

MANUTENZIONE (CLEANING)
    

Impermeabile all'acqua/Waterproof fabric
Reazione al fuoco/Fire proof norm: M2 (NFP 92503)- B2 (DIN 4102) - BS 7176 Crib 5 – IMO A652

L'articolo sopra descritto è conforme alle norme R.E.A.C.H. 1907/2006/CE The item above described comply with the norms R.E.A.C.H. 1907/2006/CE
--

Compilato da QUA – Emiss. 13/12/2013 Rev.0 - Sigla *OP*